

HandiMate[™]Optical Interconnect Maintenence Solutions



Seikoh Giken releases the latest addition to their TechMate™ line of optical connector cleaning and restoration product.

The New HandiMate™ SHM-502 enables users to clean Duplex LC and Duplex MU connectors in addition to Simplex SC, FC, ST, LC, and MU connectors with a simple, handheld method of removing all types of dust and debris from optical connectors.


The unique "Slide-Guide" connector holder in combination with the "Clean and Advance" tape technology continuously provides a fresh cleaning surface after each use.

Key Features

- Easy operation and good workability in the field thanks to its palm sized body and lightweight cleaning operation. An excellent cleaning tool for outside plant technicians.
- Stable, consistent cleaning performance regardless of operator skill thanks to its patented connector insertion "Slide-Guide" holder.
- Duplex connector cleaning in one simple operation cuts cleaning time in half greatly reducing technician's time in the field.
- Automatic "Clean and Advance" tape technology provides a fresh cleaning surface for each use eliminating waste and guaranteeing long tool life.
- Disposable with over 500 times cleaning.
- Aggressively priced when compared to other hand-held field cleaning tools.
- ESD Anti-static materials, Supports both PC and APC Endface designs.

Applications

- Customer premises troubleshooting / maintenance
- Hubsite, CO, Headend routine maintenance
- New Installation / Assembly environments





Specification/ Ordering Information


Part number	SHM-502
	*Ideal cleaner for use in data centers – Supports ESD environments
	*Cleaning work at new network construction sites
Applications	*Repair, Check and Maintenance work at Central Office facilities
	*Maintenance work at field transmission sites
	*Cleaning work for patch-cord at production assembly plants
	Duplex LC/PC (Standard Pitch 6.25 and Narrow Pitch 5.25mm)
Applicable Connector*	Duplex MU/PC (Standard Pitch width 4.5mm)
	Simplex SC, FC, ST, LC and MU (For PC and APC)
Dimension	H110×W68×D28 mm (Cap opened)
Weight	75g
Operating method	Automatic "Slide-Guide" feed system
Usable life	Over 500 times

^{*} Cannot be used with Step type APC ferrules


■ Cleaning Performance




Dust







Skin Oil









WORLDWIDE SUBSIDIARIES AND SALES OFFICES:

<u>USA</u> SEIKOH GIKEN USA, Inc.

Atlanta, Georgia Tel: +1-770-279-6602 Fax: +1-770-279-8839 sales@sg-usa.com

<u>Europe</u>

SEIKOH GIKEN Europe GmbH

Frankfurt, Germany Tel: +49-6102-297-701 Fax: +49-6102-297-750 info@sg-euro.de

<u>Asia</u>

SEIKOH GIKEN Co., Ltd.

Chiba, Japan Tel: +81-47-388-6111 Fax: +81-47-388-4477 sales.div@seikoh-giken.co.jp

