



Hybrid cable

Combicable Dca

Article number: 14828

26-07-2017

Description

Cat.6 U/UTP + MDIC 4x SM G.657.A1



Trading information

Product group	Hybrid cable
Series	Combination cable
Type	Combicable Dca
Net. Weight	0,096 kg/m
Sheath marking	TKF - COMBICABLE Cat.6 U/UTP + MDIC 4x SM G.657A LSZH 14828 {Batch} {Year} {Length}

Trade lengths

Reel à 1	(14828 / 8713182121297)
----------	-------------------------

Construction characteristics

Computer data cable (copper)	Yes
Computer data cable (fibre optic)	Yes
Core lay-up	Cat.6 UTP + MDIC 4x SM G.657A LSZH
Material outer sheath	LSZH
Colour outer sheath	White
Strip method	1 Rip cord
Application	Inside



Hybrid cable

Combicable Dca

Article number: 14828

26-07-2017

Properties

Flame retardant	Yes
Flame retardant	IEC 60332-3-24 Cat. C
Halogen free	IEC 60754-1/2
Halogen free (acc. EN 50267-2-2)	Yes
Low smoke (acc. EN 61034-2)	Yes
acidity waste gas	IEC 60754-2
Outer sheath thickness	1.0 mm
Max. outer diameter	12.5 / 8.5 mm
Diameter over assembly	10.5 / 6.5 mm
Min. bending radius during installation	250 mm
Min. bending radius after installation	160 mm
Tensile load	150 N

Technical characteristics

Transportation and storage temperature	-30 / 70 °C
Permitted cable outer temperature, in movement	0 / 50 °C
Permitted cable outer temperature, fixed	-15 / 70 °C