


**CAT6A 2X4P U/FTP LSZH Dca AWG23 White cable (500 m drum)****GGM C6AF2X4ZHT5**

Thanks to cutting edge technologies, this cable is manufactured in a way to exceed the ISO, ANSI/TIA and CENELEC for Class EA, Category 6A applications. It Can easily be integrated into a Class EA link, in order to support applications up to 10GBASE-T (10Gbits Ethernet).

It has a good shielding effectiveness with individual screened pairs (U/FTP).

Compatible with all current connecting hardware in accordance with EN 50173 and ISO/IEC 11801.

- Available packing: 305 m, 500 m and 1000 m drums
- Single and dual construction available
- Standards:
 - ISO/IEC 11801 Ed.2.2
 - EN 50173-1, EN 50173-2 et EN 50173-5
 - ISO/IEC 24764
 - IEC 61156-5 : Edition 2.0 2009-02,
 - ANSI/TIA-568-C.2
- Jacket: White RAL9003
- Overall diameter: 7.8 mm
- Insulation diameter: 1.4 mm
- Frequency range: from 0 to 550 MHz
- Characteristic impedance: 100 Ω
- Al-laminated plastic foil, on each pairs, drain wire
- Outer jacket : LSOH
 - IEC 60754-2
 - IEC 61034-2
- Fire rating :
 - EN 13501-6 : Dca s2 d2 a2
 - EN 50575
 - EN 50399
 - EN 60332-1-2
- Nominal velocity of propagation: 74 %
- Conductor bare copper wire, AWG23