



CAT6A 4P F/FTP LSZH Dca AWG23 SLIM White, (RIB 200m)

GGM C6AFF4PSHFU200



Thanks to cutting edge technologies, this cable is manufactured in a way to exceed the ISO, ANSI/TIA and CENELEC for Class EA, Category 6A applications. It Can easily be integrated into a Class EA link, in order to support applications up to 10GBASE-T (10Gbits Ethernet).

It has a good shielding effectiveness with global and individual screened pairs (F/FTP).

Compatible with all current connecting hardware in accordance with EN 50173 and ISO/IEC 11801.

Reduce the amount of cable space required in Racks and cabinets, increase cable pathway capacity.

- Packing: 200 m Reel In Box
- Standards:
 - ISO/IEC 11801 Ed.2.2
 - EN 50173-1, EN 50173-2
 - ISO/IEC 24764
 - IEC 61156-5 : (Ed 3.0)
 - ANSI/TIA-568.2-D
- Jacket: White RAL9001
- Overall diameter: 6.4mm
- Insulation diameter: 1.32 mm
- Frequency range: from 0 to 550 MHz
- Characteristic impedance: 100 ?
- Al-laminated plastic foil, global and on each pairs, with drain wire- F/FTP
- Outer jacket : LSOH
 - IEC 60754-2
 - IEC 61034-2
- Fire rating :
 - EN 13501-6 : Dca s2 d2 a2
 - EN 50575
 - EN 50399
 - EN 60332-1-2
- NVP: 78%