

EM2-R CABLE



DESCRIPTION

nVent RAYCHEM EM2-R is a small geometry robust self-regulating heating cable for simple, fast, and effective ramp heating to prevent snow and ice formation.

The self regulating EM2-R cable automatically adjusts its power output in accordance with ambient conditions; more power is produced in harsh freezing conditions and less power in marginal freezing conditions. It can be cut to length onsite providing complete flexibility in installation.

ADVANTAGES

Design phase

Designed to fit any ramp shape and size.

Variable power output to meet design requirements.

Variable lengths (cut-to-length) to precisely fit the ramp.

Installation phase

Cut to length possibility on site allows for on-site variations from design.

Small geometry makes installation of the cable easier.

Easier to install components make electrical connection and testing simple.

The applications

Car Park ramps and accessways

Footpaths and walkways

Loading Bays / Distribution centres

Airport taxi ways and aircraft stands

Emergency exits on commercial buildings

TECHNICAL DATA

Nominal Power:	80W/m at 0°C
Voltage:	230Vac
Maximum Exposure Temperature:	90°C
Dimensions:	11.8mm x 4.5mm
Circuit Breaker required:	Type C (Max. 32A.)
Maximum Circuit Length:	75m.
Cable Construction:	Self Regulating polymer heating cable, braided and overjacketed.
Certification:	CE

RELATED NVENT RAYCHEM PRODUCTS

VIA-DU-20	Programmable ramp heating control with ambient temperature, ground temperature, and moisture sensors.
CCE-04-CT	Waterproof connection and end seal kit.
JB-82	Temperature resistant junction box.

ORDER REFERENCE

EM2-R ramp heating cable is available on standard cable reels or cut to length.

Product name	Order reference	Description
EM2-R	619902-000	Self Regulating Ramp heating Cable

PRE-INSTALLATION GROUND PREPARATION

The heating cable should be installed on a stable subsurface. In suspended structures the substratum may consist of finished slabs, pre-stressed concrete or a suspended structure with poured concrete. The heating cables can be laid on all subsurfaces including reinforcement grids/bars. In the case of poured concrete, it should be ensured that the surface is smooth and all sharp objects are removed. Ramps on a solid substratum do not require any additional thermal insulation. Appropriate preparations should be made for installing the temperature and moisture sensor.

INSTALLATION INSTRUCTION

Complete installation instructions are supplied with the product and are available electronically from nVent.

United Kingdom

Tel 0800 969 013
Fax 0800 968 624
salesthermalUK@nvent.com

Ireland

Tel 1800 654 241
Fax 1800 654 240
salesIE@nvent.com

South East Asia

Tel +65 67685800
Fax +65 67322263

Australia

Tel +61 2 97920250
Fax +61 2 97745931

India - Noida

Tel +91 120 464 9500
Fax +91 120 464 9548
NTMinfome@nvent.com

India - Mumbai

Tel +91 22 6775 8800/01
Fax +91 22 2556 1491
NTMinfome@nvent.com

UAE

Tel +971 4 378 1700
Fax +971 4 378 1777
NTMinfome@nvent.com



nVent.com

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER