



SSG-E-V

**Product description:**

SSG-E-V is a hot-dip galvanised steel clamp with zinc-nickel alloy plating. It has a zinc-nickel pan-head screw M5 x 16.

This clamp is used for reliably installing Staro Gewinde-ES steel conduits and Staro Steck-ES.

**Special features**

This product is suited for the installation of circuit integrity cables (E30/ E60/ E90) and has been tested in the system.

Cat. No.:	Type	Content	PU	Weight PU/kg	Overall width mm	Overall height mm	Overall length mm	Borehole Ø mm	Recommended Distance cm
205 70 016	16	50	PCS	1,450	16,0	28,0	47,0	6,2x10	70
205 70 020	20	50	PCS	1,550	16,0	32,0	51,0	6,2x10	70
205 70 025	25	50	PCS	1,700	16,0	37,0	56,5	6,2x10	70
205 70 032	32	25	PCS	0,950	16,0	44,0	63,0	6,2x10	70
205 70 040	40	25	PCS	1,075	16,0	52,0	71,0	6,2x14	70
205 70 050	50	25	PCS	1,250	16,0	62,0	81,0	6,2x14	70
205 70 063	63	20	PCS	1,100	16,0	75,0	94,0	6,2x14	70

Standardisation

EN 61386-1:2008 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2004 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

All dimensions without tolerances are for information only.



SSG-E-V

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	• under screed
UV-resistant	DIN 53387	underground installation	• prefabricated construction
Highspeed		in concrete	• outdoor

Chemical properties	
Resistant to	oils, paint, water, weak alkalis and solvents
Limitedly resistant to	acids and strong bases
Not resistant to	sulphur

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123