


MRM 63/40

Reduction adaptor, brass nickel-plated, M63/M40



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Brass nickel-plated
Temp. range min	-200 °C
Temp. range max	250 °C
Thread type outer	M
Ø outer thread	63
Lead outer	1,5
Length screw-in thread L	10 mm
Thread type inner	M
Ø inner thread	40
Lead inner	1,5
External diameter ED	64 mm
Total length TL	14 mm
Surface	Nickel-plated
Order no. nickel-plated	10063951
Type	MRM 63/40
Packing unit	10
ETIM-Classification	EC000938

Recommended accessories

EMMU 63	10063148
ORD-E 63	10064704

15.06.2021


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice