




EN 175301-803 - M8, M9, M12, M23 & 7/8" CONNECTORS - CABLE ASSEMBLIES - DISTRIBUTION BOXES - INNOVAT


[HOME](#)
[NEW PRODUCTS](#)
[CUSTOM PRODUCTS](#)
[PART # MENUS](#)
[DOWNLOADS](#)
[FAQ](#)
[EXHIBITIONS](#)
[ABOUT US](#)
[CONTACT US](#)

HTP Product Range

- ▶ EN 175301-803 (Ex DIN 43650) Field Attachable
- ▶ EN 175301-803 (Ex DIN 43650) Moulded Cable
- ▶ EN 175301-803 (Ex DIN 43650) Special
- ▶ EN 175301-803 (Ex DIN 43650) ATEX Approved
- ▶ EN 175301-803 (Ex DIN 43650) UL/CSA Approved
- ▶ M8 Field Attachable
- ▶ M8 Moulded Cable
- ▶ M8 Panel Mounting
- ▶ M8 Distribution Boxes
- ▶ M12 Field Attachable
- ▶ M12 Moulded Cable
- ▶ M12 Panel Mounting
- ▶ Extension Cables
- ▶ M8/M12 Y & T Splitter Connectors
- ▶ M12 Distribution Boxes
- ▶ M9 Connectors
- ▶ M23 Connectors
- ▶ 7/8" Field Attachable
- ▶ 7/8" Moulded Cable
- ▶ 7/8" Panel Mounting
- ▶ 7/8" T Splitter Connectors
- ▶ Automotive
- ▶ EN 175 000
- ▶ MIL Connectors
- ▶ Fuse Holders
- ▶ Sensors Switches
- ▶ Accessories
- ▶ Cable Sleeves
- ▶ Cable Ties

DIN 43650 A Connectors Without LED & Suppression - 3 Poles



PRODUCT DESCRIPTION

Square connector Din 43650 A / ISO 4400
27,5x27,5 mm. Housing black
Type of contact: Screw with conductor protection
Contact spacing: 18 mm
Number of poles: 2poles+earth / 3poles+earth
Standard Earth Position: 12 hours
Cable Entry PG9/PG11 (unified) - 1/2 NPTF
Maximum conductor size: 1,5 mm²
Fixing Screw: M3x29,5

MATERIALS

Profile Gasket: NBR
Protection Class: IP 67 assembled

PACKAGING

50 pieces (with fixing screw and profiled gasket)

DESCRIZIONE PRODOTTO

Connettore quadrato Din 43650-A / ISO 4400
27,5x27,5 mm. Custodia nera
Tipo di contatto: vite con conduttore di protezione
Distanza tra i contatti: 18mm
Numero di poli: 2poli+terra / 3poli+terra
Posizione standard della terra: h12
Entrate cavo PG9/PG11 unificato - 1/2 NPTF
Massima sezione conduttori: 1,5 mm²
Vite di fissaggio: M3x29,5

MATERIALI

Guarnizione: NBR
Classe di protezione: IP 67 assemblato

PACKAGING

50 pezzi (con vite di fissaggio e guarniz. profilata)



G2-NU3-000

3 Poles Connector
With Pg 9/11 Cable Gland
Cable OD = .23" to .43"



G2-NF3-000

3 Poles Connector
With 1/2" NPT Threads
For Conduit Applications

HTP Connectivity LLC

300 Roundhill Drive, Unit 4
Rockaway, NJ 07866, USA
Phone: +1-973-586-2286
Fax: +1-973-586-1590
Email: info@htpconnectivity.com
Internet Site: www.htpconnectivity.com

H.T.P. High Tech Products Srl

Via Lesina no 45
24030 - Brembate di Sopra (Bergamo) - ITALY
Phone: +39.035.692509
Fax +39.035.203291
E mail: info@webhtp.eu
Internet Site: www.webhtp.eu