


Tuotetiedot					
Tuotekoodi	Tuotenimi	I_n Al	I_n Cu	U_n	
VC04-0006	Yleiskaapelikenkä 2xAl/Cu 25-120mm² eristysalustalla	380 A	400 A	690 V	
		I_{max} Al	I_{max} Cu	U_{max}	
		-	-	-	


Asennus	
Asennustapa	Ruuvi M14

OTE-yleisliittimet ovat tarkoitettu alumiini- ja kuparikaapeleiden liittämiseen.



- Poista eristys kaapelista. Ks. kuorintapituus L_1 taulukosta alapuolella.
- Poista mahdollinen oksidikerros harjaamalla.
- Sektorikaapeli on muokattava pyöreäksi ennen asennusta.
- Liitin on esirasvattu liitosrasvalla.



Kytcentä					
Ruuvien avainväli	AV	6 mm	Kaapelit	2xAl/Cu 25-120mm²	
Kirstysmomentti M	25-35 mm ²	10 Nm	Kuorintapituus	L_1	40±1 mm
	50-120 mm ²	20 Nm			
	-	-			
	-	-			



- Kiristä liitinruuvi yllämainittuun kiristysmomenttiin **M**.
- Tue liitintä kiristysten aikana.



Johdintaulukko, johtojen määrä, kpl/ kytcentätila, Al-kaapeli suluissa, Cu(Al)							
1,5 mm ²	2,5 mm ²	6 mm ²	10 mm ²	16 mm ²	25 mm ²	35 mm ²	50 mm ²
-	-	-	-	-	3(1)	3(1)	2(1)
70 mm ²	95 mm ²	120 mm ²	150 mm ²	185 mm ²	240 mm ²	300 mm ²	400 mm ²
1(1)	1(1)	1(1)	-	-	-	-	-

Ouneva Oy

Teollisuustie 21

FI-82730 Tuupovaara

Finland

Tel. +358 400 179 750

info@ouneva.fi

www.ounevagroup.fi


www.ounevaproducts.fi

Product data					
Product code	Product name	I_n Al	I_n Cu	U_n	
VC04-0006	Insulated Universal connector 2xAl/Cu 25-120mm²	380 A	400	690 V	
		I_{max} Al	I_{max} Cu	U_{max}	
		-	-	-	


Installation	
Type	Screw M14

OTE-Connectors are suitable for Aluminium- and Copper conductors.


- Strip cable, see stripping length L_1 (table below)
- Remove any layer of oxide.
- Segmental conductors have to be rounded before mounting.



Connection				
Screw head for tool	SW	6 mm	Conductors	2xAl/Cu 25-120mm²
Tightening torque M	25-35 mm ²	10 Nm	Stripping length	L_1 40±1 mm
	50-120 mm ²	20 Nm		
	-	-		
	-	-		



- Tighten the screw with torque **M**
- Support connector during tightening.



Wiring, pcs / connection, Cu(Al)							
1,5 mm ²	2,5 mm ²	6 mm ²	10 mm ²	16 mm ²	25 mm ²	35 mm ²	50 mm ²
-	-	-	-	-	3(1)	3(1)	2(1)
70 mm ²	95 mm ²	120 mm ²	150 mm ²	185 mm ²	240 mm ²	300 mm ²	400 mm ²
1(1)	1(1)	1(1)	-	-	-	-	-

Ouneva Oy

Teollisuustie 21

FI-82730 Tuupovaara

Finland

Tel. +358 400 179 750

info@ouneva.fi

www.ounevagroup.fi

www.ounevaproducts.fi