

Tuotetiedot

Tuotekoodi	VC02-0092	Sähkönumero	1914304	EAN-koodi	6410019143041
Tuotenimi	Pylväskalustesarja 3*4x50 & 6x50 6A VM			ETIM-luokka	EC000306
Johtimet	Al 50 mm ² / Cu 35 mm ²				

Tekniset tiedot

Nimellisvirta (IEC)	Cu	135	A
	Al	145	A
Nimellisjännite (IEC)		1000	V
		-	
		-	
		-	
		-	
Max. Johdinkoko		50	mm ²
Kiristysmomentti			
	1,5-2,5 mm ² (M4)	1	Nm
	2,5-16 mm ² (M10)	3	Nm
	25-50 mm ² (M10)	8	Nm
		-	
Min. Asennuslämpötila		+5	°C
Käyttölämpötila		-25...+80	°C
Paino		350	g
IP-suojaus		IP23/IP33	
Standardit	EN 61238-1:2003 ; EN 60947-7-1:2009		
Väri / Materiaali	Harmaa kotelo RAL 7035/ PA66, Tinapinnoitettu alumiininen liitinosa		
Kiinnitys / Kytkeä	Vapaasti kaapelissa		


Kuvaus

Liitinsetti sisältää 3 kpl 4x50 LED liittimiä, 1 kpl 6x50 KeVi LED liittimen, 350 mm / 16 mm² MKEM-maadoitusjohtimen PK 16-6H -haarukkakaapelikengällä, 350 mm / 2,5 mm² mustan MK-johtimen, sulakepesän 6 ampeerin sulakkeella ja alustan ruuvikiinnitystä varten. Liittimissä on vaihemerkinnät. IP-luokka on IP33, kun käytetään tiivistyspakkausta OD01-0078 ja IP23 kun käytetään ≥25 mm² johtimia suurissa johdinaukoissa ja 2,5 mm² johtimia LED-johdinaukoissa.

Mittakuva

Pakkaus

Pakkausmuoto	Laatikko	Kpl / Pakkaus	5	Paino [kg]	1,85
Pituus [mm]	295	Leveys [mm]	185	Korkeus [mm]	98

Ouneva Oy

Teollisuustie 21
 FI-82730 Tuupovaara
 Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi

Product data

Product code	VC02-0092	STK-code	1914304	EAN-code	6410019143041
Product name	Pole branching kit 3*4x50 & 6x50 6A VM			ETIM class	EC000306
Wires	Al 50 mm ² / Cu 35 mm ²				

Technical data

Nominal current (IEC)	Cu	135	A
	Al	145	A
Nominal voltage (IEC)		1000	V
		-	
		-	
		-	
		-	
Max. Cross section		50	mm ²
Tightening torque			
	1,5-2,5 mm ² (M4)	1	Nm
	2,5-16 mm ² (M10)	3	Nm
	25-50 mm ² (M10)	8	Nm
		-	
Min. installation temperature		+5	°C
Operating temperature		-25...+80	°C
Weight		350	g
IP-protection		IP23/IP33	
Standards	EN 61238-1:2003 ; EN 60947-7-1:2009		
Color / Material	Grey Housing RAL 7035/PA66, Tin plated Aluminium		
Mounting / Connection	On cable		


Description

Connector package includes 3 pieces of Al4x50/Cu4x35 grey LED connectors, 1 piece of Al6x50/Cu6x35 Ye/Gr LED connector, 350 mm / 16 mm² grounding cable with PK 16-6H fork cable shoe, 350 mm / 2,5 mm² black connector cable and 6 A fuse with base. Grey connectors are marked with live conductor markings L1-L3. IP class is IP33 when OD01-0078 sealing kit is used and IP23 when ≥25 mm² conductors are used in bigger conductor spaces and 2,5 mm² conductors in Led spaces.

Drawing

Package

Package	Box	Pcs / Package	5	Weight [kg]	1,85
Length [mm]	295	Width [mm]	185	Height [mm]	98

Ouneva Oy

Teollisuustie 21
 FI-82730 Tuupovaara
 Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi