

Tuotetiedot

Tuotekoodi	VC02-0131	Sähkönumero	1914374	EAN-koodi	6430051862151
Tuotenimi	Pylväskalustesarja johtimilla 3x 2x50 mm ² , 1x 3x50 mm ² ja 6A sulakkeella			ETIM-luokka	EC000306
Johtimet	Al 50 mm ² / Cu 35 mm ²				

Tekniset tiedot

Nimellisvirta (IEC)	Cu	135	A
	Al	145	A
Nimellisjännite (IEC)		1000	V
		-	
		-	
		-	
		-	
Max. Johdinkoko		50	mm ²
Kiristysmomentti			
	1,5-2,5 mm ² (M6)	2	Nm
	2,5-16 mm ² (M10)	3	Nm
	25-50 mm ² (M10)	8	Nm
		-	
Min. Asennuslämpötila		+5	°C
Käyttölämpötila		-25...+80	°C
Paino		463	g
IP-suojaus		IP23/IP33	
Standardit	EN 61238-1:2003 ; EN 60947-7-1:2009 ; EN 60529:1991 + A1:2000 + A2:2013		
Väri / Materiaali	Harmaa kotelo RAL 7035/ PA66, Tinapinnoitettu alumiininen liitinosa		
Kiinnitys / Kytkenä	Vapaasti kaapelissa		


Kuvaus

Liitinsetti sisältää 3 kpl 2x50 LED liittimiä, 1 kpl 3x50 KeVi LED liittimen, 350 mm / 16 mm² MKEM-maadoitusjohtimen PK 16-6H -haarukkakaapelikengällä ja 350 mm / 1,5 mm² mustan MK-johtimen, sulakepesän 6 ampeerin sulakkeella ja alustan ruuvikiinnitystä varten. IP-luokka on IP33, kun käytetään tiivistyspakkausta OD01-0078 ja IP23 kun käytetään ≥25 mm² johtimia suurissa johdinaukoissa ja 2,5 mm² johtimia LED-johdinaukoissa.

Mittakuva

Pakkaus

Pakkausmuoto	Laatikko	Kpl / Pakkaus	5	Paino [kg]	2,31
Pituus [mm]	210	Leveys [mm]	155	Korkeus [mm]	105

Ouneva Oy

Teollisuustie 21
 FI-82730 Tuupovaara
 Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi

Product data

Product code	VC02-0131	STK-code	1914374	EAN-code	6430051862151
Product name	Pole branching connector kit with conductors 3x 2x50 mm ² , 1x 3x50 mm ² \			ETIM class	EC000306
Wires	Al 50 mm ² / Cu 35 mm ²				

Technical data

Nominal current (IEC)	Cu	135	A
	Al	145	A
Nominal voltage (IEC)		1000	V
		-	
		-	
		-	
		-	
Max. Cross section		50	mm ²
Tightening torque			
	1,5-2,5 mm ² (M6)	2	Nm
	2,5-16 mm ² (M10)	3	Nm
	25-50 mm ² (M10)	8	Nm
		-	
Min. installation temperature		+5	°C
Operating temperature		-25...+80	°C
Weight		463	g
IP-protection		IP23/IP33	
Standards	EN 61238-1:2003 ; EN 60947-7-1:2009 ; EN 60529:1991 + A1:2000 + A2:2013		
Color / Material	Grey Housing RAL 7035/PA66, Tin plated Aluminium		
Mounting / Connection	On cable		


Description

Connector package includes 3 pieces of Al2x50/Cu2x35 grey LED connectors, 1 piece of Al3x50/Cu3x35 Ye/Gr LED connector, 350 mm / 16 mm² grounding cable with PK 16-6H fork cable shoe and 350 mm / 1,5 mm² black connector cable and 6 A fuse with base. IP class is IP33 when OD01-0078 sealing kit is used and IP23 when ≥25 mm² conductors are used in bigger conductor spaces and 2,5 mm² conductors in Led spaces.

Drawing

Package

Package	Box	Pcs / Package	5	Weight [kg]	2,31
Length [mm]	210	Width [mm]	155	Height [mm]	105

Ouneva Oy

Teollisuustie 21

FI-82730 Tuupovaara

Finland

Tel. +358 400 179 750

info@ouneva.fi
www.ounevagroup.fi
www.ounevaproductions.fi