



Hotel-card switch 10 AX 250 V~ can be illuminated with inscription space
2-way momentary-contact, 1-pole



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
 cream white glossy	0140 01	1	53.03	01	4010337140016
 pure white glossy	0140 03	1	53.03	01	4010337140030
 pure white matt	0140 27	1	53.03	01	4010337140276
 anthracite	0140 28	1	54.83	11	4010337140283
 colour aluminium	0140 26	1	57.61	11	4010337140269
 black matt	0140 005	1	57.61	11	4010337037170
 grey matt	0140 015	1	57.61	11	4010337077244
 stainless steel (lacquered)	0140 600	1	60.26	11	4010337021971
 bronze	0140 603	1/5	57.56	11	4010337106159



brass

0140 604

1/5

57.56

11

4010337106166



chrome

0140 605

1/5

57.56

11

4010337000884

Features

- Applications of the hotel-card switch with disassembly safeguard include performing security and energy-saving functions.
- When the hotel card is removed, any devices which are still switched on are deactivated.
- The electric circuit via the push button is only activated when the card has been inserted.

Technical data

Installation depth: 28 mm

Connections

- for rigid and flexible conductors up to: 2.5 mm²

Rated output

- LEDi/ CFLi: 100 W

Notes

- Further versions are available upon request.

Scope of supply

- Blank inscription label included.