

## SCHUKO double socket outlet 16 A 250 V~ with shutter for flush-mounted device box, 1.5-gang



| Specification                                                                                         | Order No. | Packing unit | PS | EAN           |
|-------------------------------------------------------------------------------------------------------|-----------|--------------|----|---------------|
|  cream white glossy  | 2735 01   | 10           | 01 | 4010337000822 |
|  pure white glossy | 2735 03   | 1            | 01 | 4010337771371 |
|  pure white matt   | 2735 27   | 1            | 01 | 4010337771555 |
|  anthracite        | 2735 28   | 1            | 11 | 4010337771364 |
|  colour aluminium  | 2735 26   | 1            | 11 | 4010337000785 |
|  black matt        | 2735 005  | 10           | 11 | 4010337037521 |
|  grey matt         | 2735 015  | 10           | 11 | 4010337085294 |

### Technical data

|                                       |                                            |
|---------------------------------------|--------------------------------------------|
| Installation depth:                   | 25 mm                                      |
| Connections<br>- for conductors from: | 1.5 mm <sup>2</sup> to 2.5 mm <sup>2</sup> |

## Notes

- Suitable for compact device boxes Attema UK 40 and type H 140 from ABB/HAF.
  - Increased contact protection (Safety Plus) pursuant to IEC 60884-1.
-