Data sheet



Motion detector



white EAN 4007841609313



Function description

Motion detector and photo-electric lighting controller in one. Infrared motion detector IS NM 360, for indoors and out, ideal for building fronts and driveways, 360° angle of coverage, reach up to 8 m all round, selectable time and twilight threshold, 4 function programmes geared to practical needs, with optional manual override.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	114 x 100 x 58 mm
Mains power supply	220 – 240 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Installation site	wall
Type of installation	Surface wiring
Switching zones	512 switching zones
Electronic scalability	No
Mechanical scalability	No
Optimum mounting height	2 m
Detection angle	360 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	Ø 16 m (201 m²)
Twilight setting TEACH	No
Twilight setting	2 – 1000 lx

Data sheet



Motion detector



white EAN 4007841609313

Technical specifications

Time setting	5 s – 15 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	6 pcs.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white
PU1, EAN	4007841609313