

Presence detector

HF 360 DIM EAN 4007841002831



Function description

Doesn't miss a thing. HF-presence detector Presence Control PRO HF 360 DIM for indoors, ideal for WCs with toilet cubicles, changing rooms, stairwells, multi-storey car parks, kitchens, installation height up to 3.5 m, for controlling and switching light 'ON' and 'OFF', 1 – 12 m reach, reach is electronically adjustable and can be limited in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls.

Technical specifications

Туре	Presence detector
Dimensions (L x W x H)	120 x 120 x 51 mm
Mains power supply	230 V / 50 – 60 Hz
Sensor Technology	High frequency
Application, place	Indoors
Application, place, room	side room, stairwell, washroom, wc
Installation site	ceiling
Type of installation	Concealed wiring
HF-system	5,8 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2,50 – 3,50 m
Optimum mounting height	2,8 m
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Sneak-by guard	Yes



Presence detector



DIM EAN 4007841002831

Technical specifications

Capability of masking out individual segments	Yes
Reach, detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
Reach, radial	Ø 12 m (113 m²)
Reach, tangential	Ø 12 m (113 m²)
Twilight setting TEACH	Yes
Twilight setting	100 – 1000 lx
Time setting	30 s – 30 Min.
Number of electronic ballasts, DIM interface	50
Constant-lighting control	Yes
Basic light level function	Yes
With remote control	No
Interconnection	Yes
Type of interconnection	Master/slave, Master/master
IP rating	IP20
Material	Plastic
Ambient temperature	-25 – 55 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	DIM
PU1, EAN	4007841002831



Presence detector

HF 360 DIM EAN 4007841002831

Mood image





Presence detector

HF 360 DIM EAN 4007841002831