

Presence detector

Dual HF

LiveLink

EAN 4007841 009700

STEINEL[®]
PROFESSIONAL



indoor sensor



CE

Function description

Twice as vigilant. High-frequency corridor sensor Presence Control PRO DUAL HF LiveLink for indoors, ideal for passageways and long corridors, installation height up to 3.5 m, with digital DALI interface for integration into the LiveLink system, DUAL-HF technology for radial detection of 20 m in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls, switches light 'ON' almost instantly.

Technical specifications

Type	Presence detector
Dimensions (L x W x H)	120 x 120 x 55 mm
Mains power supply	230 V / 50 – 60 Hz
Number of Dali users	8
Sensor Technology	High frequency
Application, place	Indoors
Application, place, room	corridor, aisle
Installation site	ceiling
Type of installation	Concealed wiring
HF-system	5,8 GHz
Electronic scalability	Yes
Mechanical scalability	No
Mounting height	2,50 – 3,50 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Reach, radial	20 x 3 m (60 m²)

Reach, tangential	20 x 3 m (60 m²)
Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	30 s – 60 Min.
LiveLink values	Light level, Motion detection
Constant-lighting control	No
Basic light level function	No
With bus coupling	Yes
Settings via	LiveLink app
With remote control	No
Material	Plastic
Ambient temperature	-25 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	LiveLink
PU1, EAN	4007841009700

Presence detector

Dual HF

LiveLink


EAN 4007841 009700

STEINEL[®]
PROFESSIONAL

Accessories

EAN 4007841 000363	Surface-mounting adapter Control PRO AP Box (IP54)
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 006600	HF-ceiling adapter
EAN 4007841 009151	Remote control Smart Remote

Detection Zone



Mögliche Montagehöhe: 2,50 m – 3,50 m
Orange: radial und tangential

Dimension Drawing

