

Presence detector

IR Quattro SLIM XS

LiveLink - round

EAN 4007841035235



Function description

Noticeably Inconspicuous. IR Quattro SLIM XS, the extra-slim presence detector in concealed-box format. Fits into any standard concealed box. Overall height of just 6 mm. High-precision 360° infrared sensor with globally unique retina lens and 16 sq.m square presence detection zone (4 x 4 m). Adjustment via remote control or Smart Remote.

Technical specifications

Type	Presence detector
Dimensions (Ø x H)	94 x 55 mm
Mains power supply	16 V
Power supply, detail	DALI bus
Anzahl Dali-Teilnehmer	2
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	classroom, One-person office, side room
Installation site	ceiling
Type of installation	Concealed wiring
Switching zones	408 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Sneak-by guard	Yes
Capability of masking out individual segments	No

Presence detector

IR Quattro SLIM XS

LiveLink - round

EAN 4007841035235

Technical specifications

Reach, detail	Retina lens and hexagonal Fresnel structure
Reach, radial	4 x 4 m (16 m²)
Reach, tangential	4 x 4 m (16 m²)
Reach, presence	4 x 4 m (16 m²)
Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	60 s – 60 Min.
LiveLink values	Light level, Motion detection
Constant-lighting control	Yes
Basic light level function	No
Settings via	LiveLink app
With remote control	No
Interconnection	Yes
IP rating	IP20
Material	Plastic
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	LiveLink - round
PU1, EAN	4007841035235

Mood image

