

Photo-cell controller

# Light Sensor Dual

V3 KNX - surface, rd.

EAN 4007841 058333

**STEINEL**<sup>®</sup>  
PROFESSIONAL



Twilight switch +  
eco-mode



KNX



IP54



2 - 1000 lux



ideal 4 m



5 JAHRE  
HERSTELLER  
GARANTIE  
steinel-professional.de/garantie



CE



VDE

## Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

## Technical specifications

Type	Constant-lighting controller
Dimensions (Ø x H)	126 x 56 mm
Sensor Technology	Light sensor
Application, place	outdoors, Indoors
Application, place, room	One-person office, classroom, Open-plan office, high-bay warehouse, conference room
Installation site	wall, ceiling

Type of installation	Surface wiring
Mounting height	2,00 – 4,00 m
With bus coupling	Yes
IP rating	IP54
Version	KNX - surface, rd.
PU1, EAN	4007841058333

## Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Photo-cell controller

# Light Sensor Dual

V3 KNX - surface, rd.

EAN 4007841 058333

**STEINEL**<sup>®</sup>  
PROFESSIONAL

## Dimension Drawing

