

Light Sensor Dual

V3 KNX - concealed, sq.
 EAN 4007841 058326
 Article number 058326



Twilight switch + eco-mode



KNX



IP20



2 - 1000 lux



max 4 m



CE

5 years

manufacturer's warranty
 steinel-professional.de/
 garantie

Function description

Light measurement in perfection. The Light Sensor Dual photo-cell controller with KNX interface measures directed and diffuse light, watches over areas below the sensor and measures the room brightness. Combining the measurement results reduces error influences. Available either in round or square surface-mounted and concealed version.

Technical specifications

Dimensions (L x W x H)	51 x 94 x 94 mm
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
Version	KNX - concealed, sq.
PU1, EAN	4007841058326
Type	Constant-lighting controller
Application, place	Outdoors, Indoors
Application, room	classroom, one-person office, open-plan office, high-bay warehouse, conference room / meeting room, Indoors
Colour	white
Colour, RAL	9003
Includes corner wall mount	No
Installation site	wall, ceiling
Installation	Concealed wiring, Wall, Ceiling
IP-rating	IP20

Power supply, detail	KNX bus
With bus coupling	Yes
Mounting height	2,00 – 4,00 m
Mounting height max.	4,00 m
Twilight setting	2 – 1000 lx
Basic light level function	Yes
Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Light output 2x, Light level, Constant-lighting control, Photo-cell controller, Logic gate
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	12,5 mA

Light Sensor Dual

V3 KNX - concealed, sq.
EAN 4007841 058326
Article number 058326



Technical specifications

Ambient temperature -20 – 50 °C

Dimension Drawing

