

IS 3360

V3 KNX - surface, rd. white
 EAN 4007841 058180
 Article number 058180



infrared sensor
360°



max. 20 m



KNX



IP54



2 - 1000 lux



1 - 255 min



ideal 2,5 - 4 m

Teach

Teach mode



energy saving

5 years

manufacturer's
warranty steinel-
professional.de/
garantie

Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted, concealed or In-ceiling installation.

Technical specifications

Dimensions (Ø x H)	126 x 65 mm	Optimum mounting height	2,8 m
With motion detector	Yes	Detection angle	360 °
Manufacturer's Warranty	5 years	Angle of aperture	180 °
Settings via	ETS software, Remote control, Bus, Smart Remote	Sneak-by guard	Yes
With remote control	No	Capability of masking out individual segments	Yes
Version	KNX - surface, rd. white	Electronic scalability	No
PU1, EAN	4007841058180	Mechanical scalability	No
Type	Motion and Presence Detector	Reach, radial	Ø 8 m (50 m²)
Application, place	Outdoors, Indoors	Reach, tangential	Ø 40 m (1257 m²)
Application, room	production facilities, recreation room, changing room, function room / ancillary room, sports hall, reception / lobby, stairwell, WC / washroom, multi-storey / underground car park, outdoors, warehouse, Indoors	Reach, presence	Ø 3 m (7 m²)
Colour	white	Switching zones	1416 switching zones
Colour, RAL	9003	Twilight setting	2 – 1000 lx
		Time setting	5 s – 15 Min.
		Basic light level function	Yes
		Main light adjustable	0 - 100 %
		Twilight setting TEACH	Yes

IS 3360

V3 KNX - surface, rd. white
EAN 4007841 058180
Article number 058180



Technical specifications


Includes corner wall mount	No
Installation site	ceiling
Installation	Surface wiring, Ceiling
IP-rating	IP54
Ambient temperature	-20 – 50 °C
Material	Plastic
Power supply, detail	KNX bus
With bus coupling	Yes
Technology, sensors	passive infrared, Light sensor
Mounting height	2,50 – 4,00 m
Mounting height max.	4,00 m

Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	KNX bus
Rated current	12,5 mA

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX
EAN 4007841 056735	Black cover for IR-sensors

Detection Zone



Possible mounting height: 2,50 m – 4,00 m
Orange: radial
Black: tangential

Dimension Drawing

