

Motion detector

IS 345 MX Highbay

V3 KNX - concealed, sq.

EAN 4007841 058302

STEINEL
PROFESSIONAL



infrared sensor
360°



max. 30 x 4 m



KNX



IP20



2 - 1000 lux



ideal 4 - 14 m



Teach mode



energy saving



CE



VDE

Function description

Surveillance on the highest level. Infrared motion detector IS 345 MX Highbay for indoors, ideal for large heights in depots, high-bay warehouses, machine shops, check-in areas and departure lounges, installation height 14 m, detection zone 30 x 4 m (radial), large terminal compartment for easy installation. Available as square surface-mounted and concealed version.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	94 x 94 x 78 mm
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	high-bay warehouse
Installation site	ceiling
Type of installation	Concealed wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m

Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Twilight setting TEACH	Yes
Time setting	0 s – 1092 Min.
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function
With bus coupling	Yes
Material	Plastic
Colour	white
Version	KNX - concealed, sq.
PU1, EAN	4007841058302

Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

Motion detector


IS 345 MX Highbay

V3 KNX - concealed, sq.

EAN 4007841 058302

STEINEL[®]
PROFESSIONAL

Detection Zone



Mögliche Montagehöhe: 4,00 m – 14,00 m

Orange: radial und tangential

Dimension Drawing

