Motion detector

IS 140-2 Z-Wave

black EAN 4007841 029807











1000 W max.















rgy saving

manufacture's warranty steinel.de/garantie

Function description

The classic detector, now with even more class. Infrared motion detector IS 140-2 Z-Wave, can be integrated into the Smart Friends system or any other Z-Wave network, for indoors and out, ideal for targeted detection close to the building, 140° angle of coverage, reach up to 14 m, selectable time and twilight threshold, sensor turns through 180° and tilts through 90° for exact adjustment of the detection zone.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	99 x 86 x 82 mm
Mains power supply	230 – 240 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Outdoors, Indoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall
Installation	Surface wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	1,80 – 3,00 m
Optimum mounting height	2 m
Detection angle	140 °
Angle of aperture	40 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	r = 3 m (11 m ²)

Reach, tangential	$r = 14 \text{ m} (239 \text{ m}^2)$
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs a fluorescent lamps	6 pcs.
Basic light level function	No
Functions	Sensor channel, Actuator channel
With bus coupling	No
Settings via	Z-Wave, Potentiometers
IP-rating	IP54
Material	Plastic
Colour	black
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	black
PU1, EAN	4007841029807

Motion detector

IS 140-2 Z-Wave




EAN 4007841 029807



Accessories

EAN 4007841 029876	Smartfriends Box
EAN 4007841 631864	Corner wall mount 07
EAN 4007841 631765	Corner wall mount 07

Detection Zone



Mögliche Montagehöhe: 1,80 m – 3,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

