

# IS 3360

DALI-2 APC - surface, sq.  
EAN 4007841 010560  
Article number 010560



infrared sensor  
360°



max. 20 m



IP54



2 - 1000 lux



5 sec - 15 min



manual override 4h



ideal 2,5 - 4 m

Teach

Teach mode



energy saving

5 years

manufacturer's  
warranty steinel-  
professional.de/  
garantie

## Function description

Higher, further, faster. Infrared presence detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted and concealed version.

## Technical specifications

Dimensions (L x W x H)	65 x 95 x 95 mm	Optimum mounting height	2,8 m
With motion detector	Yes	Detection angle	360 °
Manufacturer's Warranty	5 years	Angle of aperture	180 °
Settings via	Remote control, Potentiometers, Smart Remote	Sneak-by guard	Yes
With remote control	No	Capability of masking out individual segments	Yes
Version	DALI-2 APC - surface, sq.	Electronic scalability	No
PU1, EAN	4007841010560	Mechanical scalability	No
Type	Motion and Presence Detector	Reach, radial	Ø 8 m (50 m²)
Application, place	Outdoors, Indoors	Reach, tangential	Ø 40 m (1257 m²)
Application, room	production facilities, recreation room, changing room, function room / ancillary room, sports hall, reception / lobby, stairwell, WC / washroom, multi-storey / underground car park, outdoors, warehouse, Indoors	Reach, presence	Ø 3 m (7 m²)
Colour	white	Switching zones	1416 switching zones
Colour, RAL	9003	Functions	Normal / test mode, Manual ON / ON-OFF, Constant-lighting control ON-OFF
		Twilight setting	2 – 1000 lx
		Time setting	5 s – 15 Min.
		Basic light level function	Yes

# IS 3360

DALI-2 APC - surface, sq.  
EAN 4007841 010560  
Article number 010560



## Technical specifications

Includes corner wall mount	No
Installation site	ceiling
Installation	Surface wiring, Ceiling
IP-rating	IP54
Ambient temperature	-20 – 50 °C
Material	Plastic
Mains power supply	220 – 240 V / 50 – 60 Hz
Control output, Dali	Broadcast 1x30 electronic ballasts
Technology, sensors	passive infrared, Light sensor
Mounting height	2,50 – 4,00 m
Mounting height max.	4,00 m

Basic light level function time	1-30 min, all night
Main light adjustable	50 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	Cable

## Accessories


EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 559410	Service remote control RC8
EAN 4007841 592806	User remote control RC5
EAN 4007841 056711	Black cover for IR-sensors

# IS 3360

DALI-2 APC - surface, sq.  
EAN 4007841 010560  
Article number 010560




## Detection Zone




Possible mounting height: 2,50 m – 4,00 m  
Orange: radial  
Black: tangential

## Dimension Drawing



## Master circuit diagram



## Circuit diagram for interconnecting DALI-2 APC with DALI-2 IPD

