### Data sheet



Motion detector

**IS 3360** 

EAN 4007841033552



### **Functional description**

Large spaces, multi-storey car parks and production buildings with ceiling heights of up to 4 m rarely provide installation surfaces every metre. These environments call for motion detectors with a long reach. Like the IS 3360. It detects any tangential movement within an all-round distance of 20 metres. Even installed at heights of up to 4 metres. In short: one IS 3360 covers an area of more than 1000 m²! STEINEL Infrared technology that keeps its promises.

### **Technical specifications**

Туре	Motion detectors
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Type of installation	Concealed wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	Ø 40 m (1257 m²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	60 s – 255 min
KNX functions	Light output 2x, Presence output, Light level, Basic light level function, Photo-cell controller, HVAC output
With bus coupling	Yes
IP rating	IP20
Material	Plastic
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	KNX - concealed installation, round
Model	KNX

## Data sheet



Motion detector

# **IS 3360**

EAN 4007841033552

#### Sensorenerfassungsbereich 1

