Motion detector

IS 345 MX Highbay PF - concealed, sq.

EAN 4007841 033927







Function description

Surveillance on the highest level. Infrared motion detector IS 345 MX Highbay for indoors, ideal for large heights in depots, high-bay warehouses, machine shops, check-in areas and departure lounges, installation height 14 m, detection zone 30 x 4 m (radial), large terminal compartment for easy installation, heavy-duty relay for high switching capacity. Available as square surface-mounted and concealed version.

Technical specifications

Туре	Motion detectors	Reach, radial	30 x 4 m (120 m ²)
Dimensions (L x W x H)	94 x 94 x 78 mm	Twilight setting TEACH	Yes
Mains power supply	220 – 240 V / 50 – 60 Hz	Twilight setting	2 – 1000 lx
Sensor Technology	passive infrared	Time setting	5 s – 15 Min.
Application, place	Indoors	Constant-lighting control	No
Application, place, room	high-bay warehouse, indoors	Basic light level function	No
Installation site	ceiling	With remote control	No
Type of installation	Concealed wiring	Interconnection	Yes
Switching zones	280 switching zones	IP rating	IP20
Electronic scalability	No	Material	Plastic
Mechanical scalability	No	Ambient temperature	-20 – 50 °C
Mounting height	4,00 – 14,00 m	Colour	white
Optimum mounting height	12 m	Colour, RAL	9003
Detection angle	360 °	Manufacturer's Warranty	5 years
Angle of aperture	9 °	Version	PF - concealed, sq
Sneak-by guard	Yes	PU1, EAN	4007841033927
Capability of masking out indivises segments	idual Yes		



IS 345 MX Highbay PF - concealed, sq.

EAN 4007841 033927





Accessories

EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 559410	Service remote control RC8

Detection Zone

Dimension Drawing





Mögliche Montagehöhe: 4,00 m – 14,00 m Orange: radial und tangential

Master circuit diagram

