## Data sheet



Motion detector

## IS 3360 MX Highbay

EAN 4007841033613



## **Functional description**

The ceilings are generally quite high in industrial halls and business premises. Good to know then that even high ceilings do not present a problem to the IS 3360 MX Highbay. The long-reach motion detector has an extra-large detection zone and remains absolutely alert even when it is installed at a height of up to 14 metres. The IS 3360 MX Highbay is highly reliable.

## **Technical specifications**

Туре	Motion detectors
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Type of installation	Concealed wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	Ø 36 m (1018 m²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	60 s – 255 min
KNX functions	Light output 2x, Presence output, Light level, Basic light level function, Photo-cell controller, HVAC output
With bus coupling	Yes
IP rating	IP20
Material	Plastic
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	KNX - concealed installation, square
Model	KNX