### Data sheet



Motion detector

## sensIQ KNX

EVO black EAN 4007841029609



#### **Function description**

King of the infrared motion detectors. The revolutionary sensIQ KNX for indoors and out, ideal for building entrances, loading bays, installation height up to 5 m, quadruple sensor system for optimum coverage over a 300° detection angle, 20 m range (tangential), metre-precision reach setting in 3 different directions. Remote control and corner wall mount bracket included.

#### **Technical specifications**

Туре	Motion detectors
Type of accessory	Corner adapter
Dimensions (L x W x H)	144 x 113 x 172 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	multi-storey car park, underground car park
Installation site	wall, ceiling, corner
Type of installation	Surface wiring
Switching zones	304 switching zones
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,00 – 5,00 m
Optimum mounting height	2 m
Detection angle	300 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

## Data sheet



Motion detector

# sensIQ KNX

EVO black EAN 4007841029609

#### **Technical specifications**

Reach, detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)
Reach, radial	r = 20 m (1047 m²)
Reach, tangential	r = 20 m (1047 m²)
Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	60 s – 255 Min.
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function time	1-255 min
KNX functions	Light output 2x, Presence output, Light level, Constant-lighting control, Basic light level function, Photo-cell controller, Close range, Individual pyro evaluation
With bus coupling	Yes
A	
Settings via	ETS software, Remote control, Bus
With remote control	Yes
With remote control	Yes
With remote control Interconnection	Yes Yes
With remote control Interconnection IP rating	Yes Yes IP54
With remote control Interconnection IP rating Material	Yes Yes IP54 Plastic
With remote control Interconnection IP rating Material Ambient temperature	Yes Yes IP54 Plastic -20 – 50 °C
With remote control Interconnection IP rating Material Ambient temperature Colour	Yes Yes IP54 Plastic -20 – 50 °C black
With remote control Interconnection IP rating Material Ambient temperature Colour Colour, RAL	Yes Yes IP54 Plastic -20 - 50 °C black 9005
With remote control Interconnection IP rating Material Ambient temperature Colour Colour, RAL IDs, certificates	Yes  IP54  Plastic  -20 – 50 °C  black  9005  VDE
With remote control Interconnection IP rating Material Ambient temperature Colour Colour, RAL IDs, certificates Manufacturer's Warranty	Yes Yes IP54 Plastic -20 - 50 °C black 9005 VDE 5 years

# Data sheet



Motion detector

## sensIQ KNX

EVO black EAN 4007841029609

### Mood image

