

IR Quattro HD 24m DALI plus

Surface wiring
EAN 4007841 035273
Article number 035273



infrared sensor
360°



max. 8 x 8 m
presence

HD

4800 zones



ideal 2,5 - 10 m



indoor sensor



10 - 1000 lux



5 sec - 60 min

iQ

iQ-mode



energy saving

5 years

manufacturer's
warranty steinel-
professional.de/
garantie

Function description

The gateway to intelligent lighting control. Intelligent infrared presence detector IR Quattro HD DALI plus with a wide range of additional functions, ideal for classrooms, open-plan offices and multi-storey car parks, mounting height up to 10 m, with three lighting channels (DALI addressable) for up to 64 luminaires, easily set up via app. Additional floating relay, constant-lighting control and variable light-level functions, button interface for all 3 lighting channels for controlling and dimming the floating relay (lighting mode), remotely controllable via Smart Remote.

Technical specifications

Dimensions (L x W x H)	65 x 120 x 120 mm	Mounting height max.	10,00 m
With motion detector	Yes	Optimum mounting height	2,8 m
Manufacturer's Warranty	5 years	Detection angle	360 °
Settings via	Remote control, Smart Remote	Angle of aperture	160 °
With remote control	No	Sneak-by guard	Yes
Version	Surface wiring	Capability of masking out individual segments	No
PU1, EAN	4007841035273	Electronic scalability	No
Type	Presence detector	Mechanical scalability	Yes
Application, place	Indoors	Reach, radial	8 x 8 m (64 m ²)
Application, room	classroom, lecture hall, open-plan office, high-bay warehouse, production facilities, conference room / meeting room, duty room, recreation room, changing room, sports hall, reception / lobby, multi-storey / underground car park, Indoors	Reach, tangential	20 x 20 m (400 m ²)
		Reach, presence	8 x 8 m (64 m ²)
		Switching zones	4800 switching zones
Colour	white	Functions	4 inputs for conventional switches, Semi-/fully automatic, Constant-lighting control ON-OFF, Master/slave override, Neighbouring group

IR Quattro HD 24m DALI plus

Surface wiring
EAN 4007841 035273
Article number 035273



Technical specifications

Colour, RAL	9010	function, Normal / test mode, TouchDIM function
Includes corner wall mount	No	
Installation site	ceiling	Twilight setting
Installation	Surface wiring, Ceiling	10 – 1000 lx
IP-rating	IP20	Time setting
Ambient temperature	0 – 40 °C	5 s – 60 Min.
Material	Plastic	Basic light level function
Mains power supply	220 – 240 V / 50 – 60 Hz	Yes
Power consumption	0,5 W	Basic light level function time
Control output, Dali	Addressable / broadcast 64 electronic ballasts	1-60 min, all night
Technology, sensors	passive infrared, Light sensor	Main light adjustable
Mounting height	2,50 – 10,00 m	50 - 100 %
		Twilight setting TEACH
		Yes
		Constant-lighting control
		Yes
		Interconnection
		Yes
		Type of interconnection
		Master/master, Master/slave
		Interconnection via
		Cable, DALI bus

IR Quattro HD 24m DALI plus


Surface wiring

EAN 4007841 035273

Article number 035273



Detection Zone




Possible mounting height: 2,50 m - 10,00 m


Orange: presence

Black: tangential


Dimension Drawing



Master circuit diagram



Master circuit diagram with electronic ballast OFF



IR Quattro HD 24m DALI plus


Surface wiring

EAN 4007841 035273

Article number 035273



Master circuit diagram with switched luminaire



Master/slave and master/master interconnection circuit diagram

