

Hallway

BT IPD - surface
EAN 4007841 064563
Article number 064563



max. 25 x 3 m



2 - 4 m



IP54



2 - 2000 lux

5 years

manufacturer's warranty steinel-
professional.de/garantie



CE

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

Technical specifications

Dimensions (L x W x H)	62 x 123 x 123 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	Bluetooth
With remote control	No
Version	BT IPD - surface
PU1, EAN	4007841064563
Type	Presence detector
Application, place	Indoors
Application, room	Indoors, corridor / aisle
Colour	white
Colour, RAL	9003
Includes corner wall mount	No
Installation site	ceiling
Installation	Surface wiring, Ceiling
Ambient temperature	-20 – 50 °C
Material	Plastic

Mounting height max.	4,00 m
Optimum mounting height	2,8 m
HF-system	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	Aisle, 360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	25 x 3 m (75 m ²)
Reach, tangential	25 x 3 m (75 m ²)
Transmitter power	< 1 mW
Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	No

Hallway

BT IPD - surface

EAN 4007841 064563

Article number 064563




Technical specifications

Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	High frequency
Mounting height	2,00 – 4,00 m

Constant-lighting control	No
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	Bluetooth


Detection Zone



Mögliche Montagehöhe: 2,00 m – 4,00 m

Orange: radial und tangential

Dimension Drawing



Circuit diagram

