

SLC UNIVERSAL LED-DIMMER TED



Trailing Edge. 220-240VAC 50Hz. 10-350W (1.5A max). End Turning function.

Technical data	
Product ID	S56001
Dimming range	1-100% %
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Method of operation	Turn button
Colour	White
Halogen free	No
Surface protection	Untreated
Material quality	Duroplast
Type of load	Universal and LED Retrofit
Material	Plastic
Light value memory	Yes
Substation input	No
Serial dimmer	No
Applicable with movement sensor	Yes
Applicable with transmission button	No
Applicable with infrared button	No
Applicable with presence indicator	Yes
Applicable with button	No
Applicable with time switch/timer	Yes
Transparent	No
Surface finishing	Glossy
Dimming phase cut-off	Yes
Dimming phase cut-on	No
App control via Bluetooth	No
Dimming interface	Trailing edge
Input	
Nominal voltage	220 - 240 V
Frequency	50 - 60 Hz
Output	
Nominal power	10 - 350 W
Mono	Yes
Installation	



25.02.2020

Subject to changes and printing errors

Mounting method	Flush mounted (plaster)
Connection type	Screwed terminal
Min. depth of built-in installation box	25 mm
Type of fastening	Mounting with claw and screw
Core cross section	1 - 2 mm ²
Width of device	83.5 mm
Height of device	83.5 mm
Depth of device	44 mm
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938055017
Suitable for degree of protection (IP)	IP20