

DALIECO SWARM ADAPTER

DALleco Swarm Adapter | Radio adapter for DALleco Control



Product family features

- 868 MHz radio adapter for wireless synchronization of DALleco control units
- Bidirectional transmission of motion signals and central on/off commands
- Digital radio coding of up to seven zones and seven group addresses
- Transmitter range: up to 50 m
- VDE certified system
- Direct connection and supply via DALleco control unit

Product family benefits


- Simple configuration via screwdriver

Areas of application

- Offices
- Corridors

Technical data

Dimensions & weight



Length	71.0 mm
Width	30.0 mm
Height	11.0 mm
Product weight	17.00 g

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Number of control outputs	1
Type of installation	Luminaire integration
Transmitter range	50 m

Certificates & standards

Type of protection	IP20
--------------------	------

Logistical data

Commodity code	852692009000
----------------	--------------

Download Data

File	
	User instruction 726596_DALI ECO Swarm adapter mounting instruction
	User instruction 726597_DALIEco Swarm Adapter radio leaflet

Product datasheet

	User instruction 726598_DALIEco Swarm Adapter user instruction
	Brochures DALIeco: Multi-functional light management system (EN)
	Declarations of conformity EU Declaration of Conformity DALIeco Swarm Adapter

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899955646	DALIECO SWARM ADAPTER	Shipping carton box 45	320 mm x 265 mm x 160 mm	13.57 dm ³	1513.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.