

DIM MCU G2

DIM MCU | Light management systems



Product family features

- Switching load contact: 250 V/6 A (10 1-lamp or 5 2-lamp ECGs)
- Cover and rotary knob in cream white

Product family benefits

- Intuitive manual dimming and switching
- Individual setting of minimal brightness level

Areas of application


- Conference rooms
- Restaurants
- Shop lighting

Technical data

Electrical data

Nominal voltage	230 V
-----------------	-------

Dimensions & weight



Length	71.0 mm
Width	71.0 mm
Height	40.0 mm
Product weight	140.00 g
Mounting hole spacing, length	60.0 mm

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

Capabilities

Dimmable	Yes
Dimming interface	1...10 V
Number of control outputs	1
Load contact	6 A
Type of installation	Integrated in flush device box

Certificates & standards

Type of protection	IP20
Protection class	II
Approval marks – approval	CE / UKCA / EAC

Product datasheet


Logistical data

Commodity code	853650809000
----------------	--------------

Equipment / Accessories

- Suitable for up to 50 electronic control gears (external load contact required)
- Flexible expansion via external load contact and via signal amplifier DIM SA
- Cover and rotary knob included

Download Data

File	
	User instruction DIM MCU G2

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172224642	DIM MCU G2	Shipping carton box 48	362 mm x 270 mm x 288 mm	28.15 dm ³	8980.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.