



Coupling relay in industrial enclosure 3 changeover contacts Wide voltage range 24 V to 240 V AC/DC Spring-type terminals

|  |  |
|--|--|
| product brand name   | SIRIUS                                       |
| product designation  | Coupling relay in industrial enclosure       |
| product type designation   | 3RQ2   |
| <b>General technical data</b>  |  |
| consumed active power  | 5 W  |
| insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value  | 300 V  |
| degree of pollution  | 3  |
| surge voltage resistance rated value   | 4 kV   |
| maximum permissible voltage for safe isolation <ul style="list-style-type: none"> <li>between auxiliary and auxiliary circuit</li> <li>between control and auxiliary circuit according to IEC 60947-1</li> </ul> | 300 V<br>300 V                               |
| protection class IP  | IP20   |
| shock resistance <ul style="list-style-type: none"> <li>according to IEC 60068-2-27</li> <li>for railway applications according to EN 61373</li> </ul>   | 11g / 15 ms<br>Category 1, Class B           |
| vibration resistance <ul style="list-style-type: none"> <li>according to IEC 60068-2-6</li> <li>for railway applications according to EN 61373</li> </ul>  | 10 ... 55 Hz: 0.35 mm<br>Category 1, Class B |
| switching behavior   | monostable                                   |
| mechanical service life (operating cycles) typical   | 10 000 000                                   |
| electrical endurance (operating cycles) at AC-15 at 230 V typical  | 100 000                                      |
| thermal current of the switching element with contacts maximum   | 5 A  |
| reference code according to IEC 81346-2  | K  |
| Substance Prohibition (Date)   | 05/31/2018                                   |
| <b>Control circuit/ Control</b>  |  |
| control supply voltage 1 at AC <ul style="list-style-type: none"> <li>at 50 Hz</li> <li>at 60 Hz</li> </ul>  | 24 ... 240 V<br>24 ... 240 V                 |
| control supply voltage 1 <ul style="list-style-type: none"> <li>at DC</li> </ul>   | 24 ... 240 V                                 |
| operating range factor control supply voltage rated value at DC <ul style="list-style-type: none"> <li>initial value</li> <li>full-scale value</li> </ul>  | 0.7<br>1.1                                   |
| operating range factor control supply voltage rated value at AC at 50 Hz <ul style="list-style-type: none"> <li>initial value</li> <li>full-scale value</li> </ul>   | 0.7<br>1.1                                   |

|   |  |
|---|--|
| <b>operating range factor control supply voltage rated value at AC at 60 Hz</b>       |  |
| • initial value   | 0.7  |
| • full-scale value  | 1.1  |
| <b>ON-delay time</b>  |  |
| • at AC maximum   | 10 ms  |
| • at DC maximum   | 10 ms  |
| <b>OFF-delay time</b>   | 100 ms   |
| <b>design of the relay operating mechanism</b>  | poled  |
| <b>product component plug-in socket</b>   | No   |
| <b>Short-circuit protection</b>   |  |
| design of the fuse link for short-circuit protection of the auxiliary switch required | fuse gL/gG: 6 A  |
| <b>Auxiliary circuit</b>  |  |
| <b>material of switching contacts</b>   | AgSnO2   |
| <b>number of NC contacts for auxiliary contacts</b>                                   | 0  |
| <b>number of NO contacts for auxiliary contacts</b>                                   | 0  |
| number of CO contacts for auxiliary contacts  | 3  |
| <b>contact reliability of auxiliary contacts</b>                                      | one incorrect switching operation of 100 million switching operations (17 V, 5 mA) |
| <b>type of voltage</b>  | AC/DC  |
| <b>ampacity of the output relay at AC-15</b>  |  |
| • at 24 V at 50/60 Hz   | 3 A  |
| • at 110 V at 50/60 Hz  | 3 A  |
| • at 250 V at 50/60 Hz  | 3 A  |
| <b>ampacity of the output relay at DC-13</b>  |  |
| • at 24 V   | 1 A  |
| • at 125 V  | 0.2 A  |
| • at 250 V  | 0.1 A  |
| <b>Electromagnetic compatibility</b>  |  |
| EMC emitted interference according to IEC 60947-1                                     | ambience A (industrial sector)   |
| EMC immunity according to IEC 60947-1   | corresponds to degree of severity 3  |
| <b>conducted interference</b>   |  |
| • due to burst according to IEC 61000-4-4   | 2 kV   |
| • due to conductor-earth surge according to IEC 61000-4-5                             | 2 kV (line to ground)  |
| • due to conductor-conductor surge according to IEC 61000-4-5                         | 1 kV (line to line)  |
| <b>field-based interference according to IEC 61000-4-3</b>                            | 10 V/m   |
| <b>electrostatic discharge according to IEC 61000-4-2</b>                             | 4 kV contact discharging, 8 kV air discharging                                     |
| <b>Safety related data</b>  |  |
| <b>electromagnetic compatibility</b>  | IEC 60947-1 / IEC 61000-6-2 / IEC 61000-6-4  |
| <b>Connections/ Terminals</b>   |  |
| <b>product component removable terminal for auxiliary and control circuit</b>         | Yes  |
| <b>type of electrical connection</b>  | spring-loaded terminal (push-in)   |
| <b>type of connectable conductor cross-sections</b>                                   |  |
| • solid   | 0.5 ... 4 mm <sup>2</sup>  |
| • finely stranded with core end processing  | 0.5 ... 2.5 mm <sup>2</sup>  |
| • at AWG cables solid   | 20 ... 12  |
| <b>connectable conductor cross-section</b>  |  |
| • solid   | 0.5 ... 4 mm <sup>2</sup>  |
| • finely stranded with core end processing  | 2.5 mm <sup>2</sup>  |
| • finely stranded without core end processing   | 0.5 mm <sup>2</sup>  |
| <b>AWG number as coded connectable conductor cross section</b>                        |  |
| • solid   | 12 ... 20  |
| • stranded  | 12 ... 20  |
| stripped length of the cable for auxiliary and control contacts                       | 10 mm  |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | any  |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm DIN rail                                     |
| <b>height</b>   | 100 mm   |

|   |                |
|---|----------------|
| width   | 22.5 mm        |
| depth   | 90 mm          |
| <b>Ambient conditions</b>                               |                |
| installation altitude at height above sea level maximum | 2 000 m        |
| <b>ambient temperature</b>                              |                |
| • during operation                                      | -40 ... +60 °C |
| • during storage  | -40 ... +80 °C |
| • during transport                                      | -40 ... +80 °C |
| relative humidity during operation                      | 10 ... 95 %    |

|                                |     |
|--------------------------------|-----|
| <b>Certificates/ approvals</b> |     |
| General Product Approval       | EMC |



[Confirmation](#)



|                           |                   |                   |
|---------------------------|-------------------|-------------------|
| Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------|-------------------|-------------------|



[Type Test Certificates/Test Report](#)



|                   |       |         |
|-------------------|-------|---------|
| Marine / Shipping | other | Railway |
|-------------------|-------|---------|



[Confirmation](#)

[Confirmation](#)

#### Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ2000-2CW00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ2000-2CW00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ2000-2CW00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RQ2000-2CW00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ2000-2CW00&lang=en)

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ2000-2CW00/manual>



