

S12-100-/200-/110-



S12-100-230V



1-pole and 2-pole 16A/250V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18mm wide, 55mm deep.

100 % time on. Control power demand 5-6W only.

Contacts 1 NO, 2 NO, 1 NO + 1 NC.

Contact gap 3mm. Spacing of control connections/contact > 6mm.

For control voltages up to 48V AC and 110V DC suitable for SELV net.

4-pole devices S12 and devices for 25A XS12.

Retrofittable auxiliary contact KM12.

* **Non-standard control voltages:** 42, 48, 60 and 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 42, 48, 60, 110 and 220V DC.

The terminal compatible hybrid impulse switches ES12DX-UC, ES12-200-8..230V UC and ES12-110-8..230V UC may be used as well.

S12-100-12V
S12-100-230V
S12-100-8V, 24V, 12V DC, 24V DC
S12-100-*

1 NO 16 A
1 NO 16 A
1 NO 16 A
1 NO 16 A

EAN 4010312 100455
EAN 4010312 100479

S12-200-12V
S12-200-230V
S12-200-8V, 24V, 12V DC, 24V DC
S12-200-*

2 NO 16 A
2 NO 16 A
2 NO 16 A
2 NO 16 A

EAN 4010312 100530
EAN 4010312 100554

S12-110-12V
S12-110-230V
S12-110-8V, 24V, 12V DC, 24V DC
S12-110-*

1 NO + 1 NC 16 A
1 NO + 1 NC 16 A
1 NO + 1 NC 16 A
1 NO + 1 NC 16 A

EAN 4010312 100493
EAN 4010312 100516