



| | | | |
|--|--|---|--|
| <p>Note:</p> <ul style="list-style-type: none"> - Drawings Not To Scale - Drawings Subject to Change Without Notice - Dimensions are inches next to [Millimeters] | <p>Part No.:</p> <p>TM2DMM24DRF</p> | | <p>Schneider Electric United States North American Division Boston One Campus 800 Federal Street Andover, MA 01810, USA Phone: +1 8773425173 Email: CCC@us.schneider-electric.com</p> |
| <p>Isolation Between Channels and Int. Logic:</p> <p>Isolation Between Channels:</p> <p>Mounting:</p> <p>RoHS:</p> <p>Weight [kg]:</p> | <p>Technical Information:</p> <p>500V AC rms for 1min (Input), 2300V AC rms for 1min (Output)</p> <p>1500V AC rms for 1min (Output groups)</p> <p>35mm DIN Rail</p> <p>Yes</p> <p>0.14</p> | <p>Description:</p> <p>Selection:</p> <p>Input Voltage Range:</p> <p>Input Current:</p> <p>Input Logic:</p> <p>Output Logic:</p> <p>Output Current (per output/per group of channels):</p> <p>Output Logic:</p> <p>Num. of Relay Outputs:</p> <p>Response Time (Off-On/On-Off):</p> <p>Connection Type:</p> | <p>Specification:</p> <p>Digital Mixed Expansion Module</p> <p>20.4 - 28.8V DC</p> <p>7mA per channel</p> <p>Sink/Source</p> <p>240V AC, 30V DC</p> <p>Sink/Source</p> <p>4ms/4ms</p> <p>non-removable spring terminal block</p> |