


**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:

**XSAV11801TF**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Detecting Distance: 10.0 mm (0.39 in)  
 Circuit Type: 2 wire  
 Output Mode: NO  
 Volts Type: AC/DC  
 Voltage Range: 24-240  
 Max Load: AC:350 mA DC:200 mA  
 Shielding: Shielded  
 Max Switching Frequency: 6000 Hz  
 Temp Range: -40° to 70° C (-40° to 158° F)  
 NEMA Type: 4X (indoor use only)  
 IP Rating: IP67  
 Standards: UL, CE Rohs

**Specification:**

Sensor Type: Inductive  
 Description: Proximity Sensor, Inductive, 30 mm Barrel, 24-240, Shielded  
 Body Style: Barrel  
 Diameter: mm  
 Housing Material: Nickel Plated Brass  
 Cable Size: 2.0 m (6.6 ft)  
 Connector Type:  
 Special Features: Motion Detection Sensor, Low Temp Operation (-40C)