


<p>Note:</p> <ul style="list-style-type: none">- Drawings Not To Scale- Drawings Subject to Change Without Notice- Dimensions are inches next to [Millimeters]	<p>Part No.:</p> <p>XSDJ607339</p>	<p> Telemecanique Sensors</p> <p>Telemecanique Sensors 1875 Founders Drive Dayton, OH 45420-4017 Customer Care Center : 1-800-435-2121 Web : www.tesensors.com</p>
--	---	---

Technical Information:	Specification:
<p>Detecting Distance: 30.0 - 60.0 mm (1.17 - 2.34 in)</p> <p>Circuit Type: 4 wire</p> <p>Output Mode: NO/NC</p> <p>Volts Type: DC</p> <p>Voltage Range: 12-48 VDC</p> <p>Max Load: 200 mA</p> <p>Shielding: Non shielded</p> <p>Max Switching Frequency: 50 Hz</p> <p>Temp Range: -25° to 70° C (-13° to 158° F)</p> <p>NEMA Type: 4X (indoor use only)</p> <p>IP Rating: IP67</p> <p>Standards: UL, CE Rohs</p>	<p>Sensor Type: Inductive</p> <p>Description: Proximity Sensor, Inductive, Flat Profile, 12-48 VDC, Non shielded</p> <p>Body Style: Flat Profile</p> <p>Diameter: 2.96 inches [75.2 mm]</p> <p>Housing Material: Thermoplastic Polyester</p> <p>Cable Size: 2.0 m (6.6 ft)</p> <p>Connector Type: 4xø0.21 [5.3]</p> <p>Special Features:</p>