


<div>Note:<ul style="list-style-type: none">- Drawings Not To Scale- Drawings Subject to Change Without Notice- Dimensions are inches next to [Millimeters]</div>		<div>Part No.:<div>XS9E11RPBL01M12</div></div>		<div><div><div>Telemecanique</div><div>Sensors</div></div><div>Telemecanique Sensors 1875 Founders Drive Dayton, OH 45420-4017 Customer Care Center : 1-800-435-2121 Web : www.tesensors.com</div></div>	
<div>Technical Information:</div> <div><div>Detecting Distance:8.0 mm (0.31 in)</div><div>Circuit Type:PNP</div><div>Output Mode:NO</div><div>Volts Type:DC</div><div>Voltage Range:12-24 VDC</div><div>Max Load:</div><div>Shielding:Shielded</div><div>Max Switching Frequency:1000 Hz</div><div>Temp Range:-25° to 70° C (-13° to 158° F)</div><div>NEMA Type:4X (indoor use only)</div><div>IP Rating:IP67</div><div>Standards:UL, CE Rohs</div></div>				<div>Specification:</div> <div><div>Sensor Type:Inductive</div><div>Description:Proximity Sensor, Inductive, Flat Profile, 12-24 VDC, Shielded</div><div>Body Style:Flat Profile</div><div>Diameter:</div><div>Housing Material:Polybutylene Terephthalate</div><div>Cable Size:</div><div>Connector Type:M12</div><div>Special Features:Motion Detection Sensor</div></div>	