


KNX IP router



| Specification | Order No. | Packing unit | £/piece without VAT | PS | EAN |
|---|-----------|--------------|------------------------|----|---------------|
|  DRA plus | 2167 00 | 1 | 407.30 | 26 | 4010337084440 |

Features

- Connection of KNX lines with aid of data networks and use of the Internet protocol (IP).
- Coupling of a KNX system together with the Gira HomeServer or Gira FacilityServer.
- Filtering and forwarding of telegrams.
- Use as line or area coupler.
- Use as KNX clock.
- Recording of KNX telegrams on a microSD card.
- KNX Data Secure and KNX IP Secure for secure and tamper-proof communication in KNX.
- Up to four tunnelling connection possible simultaneously.
- Reliable communication for automatic correction of telegram losses in WLAN (Reliable Communication).

Technical data

| | |
|----------------------|---|
| KNX medium: | KNXnet/IP and TP1-256 |
| Rated voltage: | DC 24 to 30 V |
| IP communication: | Ethernet 10/100 BaseT (10/100 Mbit/s) |
| Supported protocols: | ARP, ICMP, IGMP, DHCP, AutoIP, UDP/IP (Core, Routing, Tunneling, Device Management) |
| microSD card: | up to 32 GB |
| Connections | |
| - IP: | RJ45 jack |
| - KNX: | Connection and junction terminal |
| Ambient temperature: | 0 °C to +45 °C |

Notes

- Supply via external DC 24 V.
 - The Gira Project Assistant (GPA) is required for firmware updates. The GPA is available free of charge in the Gira download area.
-

Scope of supply

- microSD card is not included in the scope of supply.
-

Dimensions

Modular widths (MW): 2
