


## KNX weather station Standard



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
	2150 04	1	570.85	06	4010337058441

## Features

- Weather station Standard for measuring and evaluating weather data (wind speed, precipitation, twilight, temperature, and brightness).
- Installation outdoors of buildings, preferably in the roof area.
- Temperature sensor for measuring the outdoor temperature.
- Wind sensor (thermal) for determining the wind speed.
- Twilight sensor for measuring the brightness in the twilight range.
- Three brightness sensors offset by 90° determine the brightness in daylight and sunshine, direction-dependent.
- Rain sensor for recording precipitation.
- A teach-in function enables the application of a current measured value as a limit. This can, for example, be triggered by pressing an external button.
- Two limits with an adjustable hysteresis per sensor (except rain sensor) can be parameterised.
- All limit objects have a parameterisable switch-on and switch-off delay.
- Six logic gates (AND, AND with return, OR, Exclusive OR, NAND, NOR) with up to four inputs for external and internal 1 bit values.
- Four blocking elements for blocking functions or manual operation.
- Cyclical transmission in case of a value change.

## Technical data

KNX medium:	TP1-64
Rated voltage:	AC/DC 24 V SELV
Power consumption:	7 W
Measurement range	
- Wind speed:	0 to 40 m/s
- Brightness:	1 to 110 klx
- Twilight:	0 to 674 lux
- Precipitation:	Yes/No (binary)
Protection type:	IP44
Ambient temperature:	-20 °C to +55 °C

## Notes

- Direct sunlight can impact temperature measurement.
-