

Bluetooth wall transmitter, 1-gang



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
pure white glossy	2461 03	1	77.40	02	4010337101598
pure white matt	2461 27	1	77.40	02	4010337101604
anthracite	2461 28	1	79.20	02	4010337101611
colour aluminium	2461 26	1	81.90	02	4010337101628
black matt	2461 005	1	81.90	02	4010337101635

Features

- Wireless transmitter for the transmission of switching, dimming and blind commands to a wireless bluetooth receiver.
- Battery-free device without external voltage supply. Transmission energy is generated from mechanical energy by actuating the rocker.

Technical data

Wireless frequency:	2,402 - 2,480 GHz
:	
Range	
- in free field:	up to 75 m
- in buildings:	approx. 10 m
Ambient temperature:	-25 °C to +65 °C
Humidity:	0 to 95 % (without condensation)

Notes

- Installation to device box or to smooth, level surfaces using screws or adhesives.
- This product cannot be used with eNet. Gira Bluetooth transmitters are compatible with third-party actuators, e. g. Casambi.

Scope of supply

- Wireless wall transmitter, comes with mounting plate, adhesive film (privacy protection for glass surfaces), and adhesive points for installation on smooth, level surfaces.
-