

DualTech

V3 KNX - in-ceiling installation
EAN 4007841 079581
Article number 079581



ultrasonic sensor
360°



infrared sensor
360°



max. Ø 6 m
presence



KNX 4 channel



IP20



ideal 2,5 - 3,5 m



indoor sensor



iQ-mode



Teach mode



energy saving

Function description

The best of both worlds. Combined in one detector. Ultrasonic presence detector DualTech KNX, ideal for offices, conference rooms and class rooms. 36 sq.m. presence zone, ultrasonic technology provides reliable detection behind objects regardless of temperature, additional detection capability with PIR technology, electronic adjustment for ultrasonic reach, with digital BUS interface for controlling 4 lighting channels and HVAC.

Technical specifications

Dimensions (L x W x H)	103 x 120 x 120 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
Version	KNX - in-ceiling installation
PU1, EAN	4007841079581
Type	Presence detector
Application, place	Indoors
Application, room	classroom, one-person office, open-plan office, conference room / meeting room, duty room, recreation room, Indoors
Colour	white
Colour, RAL	9010
Includes corner wall mount	No
Installation site	ceiling
Installation	In-ceiling installation, Ceiling

Optimum mounting height	2,8 m
Ultrasonic technology	40 kHz
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 10 m (79 m²)
Reach, tangential	Ø 10 m (79 m²)
Reach, presence	Ø 6 m (28 m²)
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Basic light level function	Yes
Basic light level function time	1-255 min
Main light adjustable	0 - 100 %

DualTech

V3 KNX - in-ceiling installation
EAN 4007841 079581
Article number 079581



Technical specifications

IP-rating	IP20
Ambient temperature	-25 – 55 °C
Material	Plastic
Mains power supply	30 V
Power consumption	0,7 W
With bus coupling	Yes
Sensor Technology	Ultrasonic, Passive infrared
Mounting height	2,50 – 3,5 m
Mounting height max.	3,50 m

Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	17,5 mA

Accessories

EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX


DualTech

V3 KNX - in-ceiling installation

EAN 4007841 079581

Article number 079581

Detection Zone




Mögliche Montagehöhe: 2,50 m – 3,50 m

Orange: Präsenz und tangential

Schwarz: radial

Dimension Drawing 1



Dimension Drawing 2

