

# HF 360

V3 KNX - in-ceiling installation  
EAN 4007841 079536  
Article number 079536



Hochfrequenz  
Sensor 360°



Max. Ø 12 m



KNX 4 Kanal



IP20



Ideal 2,5 - 3,5 m



Innen-  
Bewegungsmelder



iQ-mode



Teach mode



Energie sparen



5 years  
Herstellergarantie  
steinel-  
professional.de/  
garantie

## Function description

Doesn't miss a thing. HF-presence detector Presence Control PRO HF 360 KNX for indoors, ideal for WCs with toilet cubicles, changing rooms, stairwells, multi-storey car parks, kitchens, installation height up to 3.5 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 1 – 12 m reach, reach is electronically adjustable and can be limited in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls.

## Technical specifications

Dimensions (L x W x H)	94 x 120 x 120 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Version	KNX - in-ceiling installation
PU1, EAN	4007841079536
Type	Presence detector
Application, place	Indoors
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9010
Includes corner wall mount	No
Installation site	ceiling

HF-system	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 12 m (113 m²)
Reach, tangential	Ø 12 m (113 m²)
Abdeckmaterial Lieferumfang	sticker
Transmitter power	< 1 mW
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Basic light level function	Yes

# HF 360

V3 KNX - in-ceiling installation  
EAN 4007841 079536  
Article number 079536



## Technical specifications

Installation	In-ceiling installation, Ceiling
IP-rating	IP20
Ambient temperature	-25 – 55 °C
Material	Plastic
Mains power supply	30 V
Power consumption	0,7 W
With bus coupling	Yes
Technology, sensors	Photo-cell controller, High frequency
Mounting height	2,50 – 3,5 m
Mounting height max.	3,50 m
Optimum mounting height	2,8 m

Basic light level function time	1-255 min
Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	30 mA

## Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX


# HF 360

V3 KNX - in-ceiling installation

EAN 4007841 079536


Article number 079536

## Detection Zone



Possible mounting height: 2,50 m – 3,50 m  
Orange: radial and tangential

## Dimension Drawing 1



## Dimension Drawing 2

