Presence detector - Professional Line



BT IPD - surface EAN 4007841 064426 Article number 064426







Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 4 m. Reach: 12 m.

Technical specifications

Dimensions (L x W x H)	57 x 123 x 123 mm	Mounting height	2,50 – 4,00 m
With motion detector	Yes	Mounting height max.	4,00 m
Manufacturer's Warranty	5 years	Optimum mounting height	2,8 m
Settings via	Bluetooth	HF-system	5,8 GHz
With remote control	No	Detection also through walls	also through glass, wood and stud
Version	BT IPD - surface		
PU1, EAN	4007841064426	Detection angle	360 °
Туре	Presence detector	Angle of aperture	140 °
Application, place	Indoors	Sneak-by guard	Yes
	function room / ancillary room,	Capability of masking out individual segments	No
		Electronic scalability	Yes
Colour	white	Mechanical scalability	No
Colour, RAL	9003	Reach, radial	Ø 12 m (113 m ²)
Includes corner wall mount	No	Reach, tangential	Ø 12 m (113 m ²)
Installation site	ceiling	Transmitter power	< 1 mW
Installation	Surface wiring, Ceiling	Basic light level function	No

Presence detector - Professional Line

HF 360-2

BT IPD - surface EAN 4007841 064426 Article number 064426

.- steinel

Technical specifications

IP-rating	IP54	
Ambient temperature	-25 – 50 °C	
Material	Plastic	
Mains power supply	220 – 240 V / 50 – 60 Hz	
Power consumption	0,5 W	
Sensor Technology	High frequency	

No	
No	
No	
Yes	
Master/slave	
Bluetooth	


Presence detector - Professional Line

HF 360-2

BT IPD - surface EAN 4007841 064426 Article number 064426




Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m Orange: radial und tangential

Circuit diagram



Dimension Drawing

