

IS 345

V3 KNX - surface, rd. black
EAN 4007841 084158
Article number 084158



infrared sensor
360°



max. 20 x 4 m



KNX



IP54



2 - 1000 lux



1 - 255 min



ideal 2,5 - 5 m

Teach

Teach mode



energy saving

5 years

manufacturer's
warranty steinel-
professional.de/
garantie

Function description

Technical specifications

Dimensions (Ø x H)	126 x 65 mm
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	No
Version	KNX - surface, rd. black
PU1, EAN	4007841084158
Type	Motion detectors
Application, place	Outdoors, Indoors
Application, room	corridor / aisle, multi-storey / underground car park, outdoors, Indoors
Colour	black
Colour, RAL	9005
Includes corner wall mount	No
Installation site	ceiling
Installation	Surface wiring, Ceiling
IP-rating	IP54
Ambient temperature	-20 – 50 °C

Mounting height max.	5,00 m
Optimum mounting height	2,5 m
Detection angle	Aisle, 360 °
Angle of aperture	45 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	12 x 6 m (72 m²)
Reach, tangential	23 x 6 m (138 m²)
Switching zones	280 switching zones
Twilight setting	2 – 1000 lx
Time setting	5 s – 15 Min.
Basic light level function	Yes
Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes

IS 345

V3 KNX - surface, rd. black
 EAN 4007841 084158
 Article number 084158




Technical specifications

Material	Plastic
With bus coupling	Yes
Mounting height	2,50 – 5,00 m

KNX functions
 Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 2x, Presence output, Day / night function, Logic gate

Rated current	12,5 mA
---------------	---------

Detection Zone



Possible mounting height: 2,50 m – 5,00 m
 Orange: radial
 Black: tangential

Dimension Drawing

