

DALI MCU TW G2

DALI MCU Tunable White | Light management systems



Product family features

- Up to 4 DALI MCU TWs can be connected in parallel to set up multiple control points
- Automatic synchronization between the control points
- Cover and rotary switch in neutral white
- Length of the DALI control cable: up to 300 m

Product family benefits

- Intuitive manual dimming, switching and changing of colour temperature
- Individual setting of minimal brightness level
- Individual setting of colour temperature range

Areas of application


- Conference rooms
- Restaurants
- Shop lighting
- Private homes

Technical data

Electrical data

Nominal voltage	230 V
-----------------	-------

Dimensions & weight



Length	71.0 mm
Width	71.0 mm
Height	50.0 mm
Product weight	98.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

Capabilities

Dimmable	Yes
Dimming interface	DALI-2
Number of control outputs	1
Type of installation	Integrated in flush device box

Certificates & standards

Type of protection	IP20
Protection class	II
Approval marks – approval	CE / UKCA / EAC

Logistical data


Product datasheet

Commodity code	853650809000
----------------	--------------

Equipment / Accessories

- Suitable for up to 25 electronic control gears
- Cover and rotary knob included

Download Data

File	
	User instruction DALI MCU TW G2

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172224673	DALI MCU TW G2	Shipping carton box 48	362 mm x 270 mm x 288 mm	28.15 dm ³	6964.00 g

- The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.