




30 000 769 - 1



Wireless sensors

Remote control FF8



Temperature at mounting location:
-20°C up to +50°C.
Storage temperature: -25°C up to +70°C.
Relative humidity:
annual average value <75%.

Wireless remote control 185x50 mm, 17mm high.

The **batteryless remote control FF8** contains two identical wireless modules the same as the cordless wireless pushbuttons FT55 and has 2 double rockers. It can transmit 8 evaluable wireless telegrams.

The top is painted in aluminum and the bottom and the rockers have an anthracite-soft paint.


For wall mounting a wall holder WHF-al and 2 stainless-steel countersunk screws 2,9x25 mm and plugs 5x25 mm are enclosed.

The rockers can be easily removed and replaced with laser engraved rockers.

Compared to the wireless pushbuttons and hand-held transmitters the wireless modules are rotated 90° to the left. Therefore the upper half of the rocker corresponds to the right half of the pushbutton and the hand-held transmitter.

This must be considered when teaching-in in wireless actuators.

If wireless modules will be exchanged, the label 0 has to be on the left.

The wireless modules integrated in the remote control can be taught-in encrypted in all encryptable actuators of the Series 61, 62 and 71 as well as the FAM14. This requires the FTVW wireless pushbutton encryption rocker. Encryptable actuators bear the pictogram .

Teaching-in wireless sensors in wireless actuators

All sensors must be taught-in in the actuators so that they can detect and execute commands.

The teach-in process is described in the operating instructions of actuators.



enocean®

THE UNIQUE WIRELESS **PROFESSIONAL
SMART HOME STANDARD**

Frequency	868.3 MHz
Transmit power	max. 10 mW

Hereby, Eltako GmbH declares that the radio equipment type FF8 is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity is available at the following internet address: https://www.eltako.com/fileadmin/downloads/en/Declaration_of_conformity/FF8_gb.pdf

WEEE registration number DE 30298319

Must be kept for later use!

Eltako GmbH

D-70736 Fellbach

Technical Support English:

 +49 711 94350025

 technical-support@eltako.de

eltako.com

48/2020 Änderungen vorbehalten.