



T R A C K

SUITABLE FOR THE FOLLOWING TRACKS: NA GLOBALTRAC PRO, CONCORD, EUTRAC 25101, HOFFMEISTER, IG STD 677, IVELA, STUCCHI, UNIPRO T3



AIR FLOW
APP DEVICE
IOT 4.0
SMART CONTROL
FILTERS
NOISE
RATED VOLTAGE
POWER CONSUMPTION
ROOM COVERAGE
AIR QUALITY SENSOR

PURE VERSION
126 m³/h
×
×
×
PREFILTER (DUST CAPTURE) TiO ₂ FILTERS + UV-A LED
from 15 dBA to 50 dBA
220 ÷ 240 Vac
38 W
UP TO 150 m² *
×

SMART VERSION
126 m³/h
iOS & ANDROID
✓
CASAMBI 
PREFILTER (DUST CAPTURE) TiO ₂ FILTERS + UV-A LED
from 15 dBA to 50 dBA
220 ÷ 240 Vac
38 W
UP TO 150 m² *
TEMPERATURE - HUMIDITY PRESSURE - TVOC CO2 rel. - IAQ - AIR FLOW

Premium VERSION
126 m³/h
iOS & ANDROID
✓
CASAMBI 
PREFILTER (DUST CAPTURE) TiO ₂ FILTERS + UV-A LED
from 15 dBA to 50 dBA
220 ÷ 240 Vac
38 W
UP TO 150 m² *
TEMPERATURE - HUMIDITY PRESSURE - TVOC CO2 rel. - IAQ - AIR FLOW INFLAMMABLE GAS - PM10

VERSION AVAILABLE AT THE END OF 2021

(*) The flow rate is indicative, as it varies according to the type of environment / ventilation present.
The data shown refers to an open space (ceiling 3m / h) and with forced ventilation (e.g. shops / offices)