

[NEOZED-Sicherungseinsatz], D02, 20 A, [gG], Un AC: 400 V, Un DC: 250 V, [mit verzinnnten Kontaktkappen]



Model	
Product brand name	SETRON
Product designation	NEOZED fuse link
Design of the product	With tin-coated contact caps
Product variations	Pack of 10
Design of the fuse link	NEOZED fuse link
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D02
Operating class of the fuse link	gG
Supply voltage	
Current / at AC / rated value	20 A
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Operating voltage / rated value	400 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA

Dissipation

Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.5 W
--	-------

Main circuit

Operating current / rated value	20 A
---------------------------------	------

Appearance

Color coding of the fuse link	Blue
Maximum short-circuit current breaking capacity (Icu) / at AC / rated value	50 kA
Mounting position	Any, preferably vertical
Net weight	13 g
Ambient temperature	-5 ... +40 °C
Environmental category	Up to 45°C at 95 % rel. humidity

Certificates

Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval

Declaration of Conformity

Test Certificates



ÖVE



VDE



EG-Konf.

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

[Miscellaneous](#)

other

[Environmental Conformations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2320>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2320>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2320

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

