



Fuse-link, low voltage, 40 A, AC 690 V, 120 kA, NH000, gL/gG, IEC, dual indicator, live gripping lugs

Part no. **NH FUSE 40AMP 690V SIZE 000 GG MGL**
Catalog No. **40NHG000B-690**

EL-Nummer
(Norway) **1664104**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	40
Rated voltage			AC 690 V
Construction size			NH000
Utilization category			gL/gG
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			NH000
Rated current		A	40
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No